# **Prismalette 360**



#### Vandal-resistant circular luminaires

Circular luminaires with high efficiency satin diffuser suitable for internal or external use. Strong high-pressure die-cast aluminium body with flame-retardant polycarbonate cover. Microwave presence detector, photocell and maintained emergency versions available.

Applications: internal and external lighting for communal residential buildings, security lighting, roof top, public staircases, pathway highlighting for schools, hospitals and other public buildings.

- Strong high-pressure die-cast LM6 aluminium body and bezel
- Plain or hooded options with high efficiency fire-retardant satin polycarbonate diffuser
- Concealed tamper-resistant cover screws as standard
- Optional photocell control
- Optional bezel trim for semi-recessed mounting
- Complies with M.O.D. JSP482 Chapter 8 Document for 'Category C' areas
- Microwave presence detector versions with stand-by light level feature
- SmartScan Radar versions with sensor discretely hidden behind the cover





Specification			
Mounting	Surface	IP rating	IP66
Impact rating	IK11	Max presence detection height	2.4 m
Lighting			
Optic	Satin diffuser	Lumen output	640 lm - 2,245 lm
Efficacy	Up to 118.2 LL/CW		
Emergency data			
Emergency lumen output	350 lm - 360 lm	Emergency type	Maintained
Emergency duration	3 hours	Battery specification	Lithium Iron Phosphate (LiFePO4)
Power			
LED power	4 W - 16 W	Circuit power	6 W - 19 W

1

# **Prismalette 360**



#### LED characteristics

CRI Rated life (hours)	80+ 100 K - L80/B10	Colour temperature	4000 K
Compliance			
UKCA	Yes	CE	Yes
C-Tick (Aus)	Yes	MOD compliance	JSP482 Chapter 8 Document for 'Category C' areas

### Dimensions



**Click or scan here** View Prismalette 360 variants using our online filtering tool



Information is correct as of 16 Jan 2025, however must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice.